



















AVENTURA WOOD



	Gauge	EN ISO 24346 (EN 428)	3.0mm
	Wear Layer	EN ISO 24340 (EN 429)	0.7mm
	Plank Size	EN ISO 24342 (EN 427)	24 @ 152.4 x 914.4mm = 3.34m ² 14 @ 203.2 x 1219.2mm = 3.46m ² 12 @ 184.2 x 1524mm = 3.37m ² 11 @ 203.2 x 1524mm = 3.41m ²
	Tile Size	EN ISO 24342 (EN 427)	9 @ 609.6 x 609.6mm = 3.34m ² 18 @ 304.8 x 609.6mm = 3.34m ² 12 @ 304.8 x 914.4mm = 3.34m ² 8 @ 457.2 x 914.4mm = 3.34m ² 6 @ 914.4 x 914.4mm = 5.01m ² 6 @ 609.6 x 1219.2mm = 4.46m ²
	Total Weight	EN ISO 23997 (EN 430)	5100g/m ²
	General Performance	EN 649 EN ISO 10582	Conforms Conforms
	Use Area	EN ISO 10874 (EN 685)	
	Reaction to Fire	EN 13501-1	Class Bfl-S1
	Abrasion Resistance	EN 660-2 EN ISO 10582	Group T Type I
	Slip Resistance	EN 13893 DIN 51130 AS 4586	Class DS (dry condition) R10 R10
			For safety flooring with sustainable wet slip resistance, refer to Expona Control or the Polysafe ranges.
	Residual Indentation	EN ISO 24343-1 (EN 433)	<0.1mm
	Dimensional Stability	EN ISO 23999 (EN 434)	≤0.1% max
	Thermal Conductivity	ISO 1264-2	Suitable for underfloor heating. Max 27°C.
	Light Fastness	ISO 105-B02	(Method 3) ≥6
	Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
	Electrical Behaviour (body voltage)	EN 1815	≤2kV Classified as 'antistatic'
	VOC Emissions	Indoor Air Comfort GOLD AgBB VOC test FloorScore Finnish M1 Afsset	Eurofins certified product Very low emissions Certified product Pass A+
	Responsible Sourcing	BES 6001 SA 8000	Good Approved factory

