

# Aventura Stone PUR

## PRODUCT SPECIFICATION

### Características

- > Madera, piedra y diseños abstractos
- > Múltiples tamaños de tablonos y baldosas
- > Accesorios de incrustación para diseños a medida
- > Bajas emisiones de COV
- > Uso comercial y residencial intensivo



Product Format	Standard	Result
Gauge	ISO 24346 (EN 428)	3.0mm
Wear Layer	ISO 24340 (EN 429)	0.70mm
Total Weight	ISO 23997 (EN 430)	5100g/m <sup>2</sup>
Finish		PUR

Plank & Tile Sizes	Size	Shades	Quantity per Box	Coverage per Box/Roll
Plank	152.4mm x 914.4mm	1	24	3.34m <sup>2</sup>
	203.2mm x 1219.2mm	2	14	3.46m <sup>2</sup>
	184.2mm x 1524mm	7	12	3.37m <sup>2</sup>
	203.2mm x 1524mm	4	11	3.41m <sup>2</sup>
Tile	609.6mm x 609.6mm	3	9	3.34m <sup>2</sup>
	304.8mm x 609.6mm	3	18	3.34m <sup>2</sup>
	304.8mm x 914.4mm	2	12	3.34m <sup>2</sup>
	457.2mm x 914.4mm	1	8	3.34m <sup>2</sup>
	914.4mm x 914.4mm	3	6	5.01m <sup>2</sup>
	609.6mm x 1219.2mm	4	6	4.46m <sup>2</sup>

Performance Requirements	Standard	Result
General Performance	ISO 10582 (EN 649) ASTM F1700	Conforms Class III Type A+B
Use Area	ISO 10874 (EN 685)	23, 34, 43
Slip Resistance	EN 13893 DIN 51130 / DIN EN 16165 Ann. B AS 4586 ASTM D2047	Class DS R10 R10 SCOF ≥0.5
Binder Content	ISO 10582	Type I
Abrasion Resistance	EN 649	Group T

<b>Reaction to Fire</b>	EN 13501-1 ASTM E662 ASTM E648 CAN/ULC S102.2 AS ISO 9239-1	Class Bfl-S1 <450 Pass Class 1 FSV < 300; SDV < 500 ≥8kW/m <sup>2</sup>
<b>Static Electrical Propensity</b>	EN 1815	≤2.0kV Classified as 'antistatic'
<b>Residual Indentation</b>	ISO 24343-1 ASTM F970 ASTM F1914	<0.05mm* ≤0.005" @ 750psi ≤0.005"
<b>Castor Chair (continuous use)</b>	ISO 4918 (EN 425)	Suitable
<b>Dimensional Stability</b>	ISO 23999 (EN 434) ASTM F2199	≤0.10%* Pass
<b>Flexibility</b>	ASTM F137	1" - Pass
<b>Underfloor Heating</b>		Suitable, max 27°C
<b>Light Fastness</b>	ISO 105-B02 (Method 3)	≥6
<b>Resistance to Light</b>	ASTM F1515	ΔE ≤ 8.0 - Meets
<b>Resistance to Heat</b>	ASTM F1514	ΔE ≤ 8.0 - Meets

\*Average test value from current production.

## Sustainability

	Standard	Result
<b>BRE Green Guide</b>		A+ ENP 429
<b>GreenTag</b>	GreenRate™	Level A
<b>Product Specific EPD</b>	EN 15804+A2	Available
<b>Recyclable</b>		100%
<b>Recycled Content</b>		Up to 40%
<b>REACH</b>		Compliant
<b>Indoor Air Comfort Gold</b>		Eurofins certified product
<b>FloorScore</b>		Certified
<b>Finnish M1 Classification</b>		Certified
<b>AgBB/ABG</b>		Pass
<b>Responsible Sourcing</b>	BES 6001 SA 8000	Very good Approved factory

## Acoustic Performance

	Standard	Result
<b>Impact Sound Reduction</b>	ISO 10140-3	9dB
<b>Sound Transmission Coefficient</b>	ASTM E90/492	STC 55
<b>Impact Insulation Class</b>	ASTM E90/492	IIC 36

## Maintenance Performance

	Standard	Result
<b>Resistance to Chemicals</b>	ISO 26987 (EN 423) ASTM F925	Good resistance Good resistance

Regular light maintenance is more cost-effective than periodic heavy maintenance and more beneficial to the floor covering.



BS EN 14041



EN 14041