

BOSQUE FX PU



	Gauge	ISO 24346 (EN 428)	2.0mm
	Wear Layer	ISO 24340 (EN 429)	0.70mm
	Roll Size	ISO 24341 (EN 426)	2m x 20m = 40m ²
	Total Weight	ISO 23997 (EN 430)	2660g/m ²
	General Performance	ISO 10582 (EN 649) ASTM F1303	Conforms Type I, Grade I, Class B Backing
	Use Area	ISO 10874 (EN 685)	
	Impact Sound Reduction	ISO 10140-3	4dB
	Binder Content	ISO 10582	Type I
	Resistance to Chemicals	ISO 26987 (EN 423) ASTM F925	Good Good
	Bacterial Resistance	ISO 846 Part C	Does not favour growth
	Reaction to Fire	EN 13501-1 ASTM E648 CAN/ULC S102.2	Class Bfl-S1 Class 1 FSV < 300; SDV < 500
	Abrasion Resistance	EN 649	Group T
	Slip Resistance*	EN 13893 AS 4586 ASTM D2047 DIN 51130 / DIN EN 16165 Ann. B	Class DS R10 SCOF ≥ 0.5 R10
	Residual Indentation	ISO 24343-1 (EN 433) ASTM F1914 ASTM F970 (Modified)	≤ 0.10mm < 0.005" < 0.005" (750 psi)
	Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
	Dimensional Stability	ISO 23999 (EN 434)	≤ 0.40%
	Flexibility	ISO 24344 (EN 435) (Method A) ASTM F137	Pass 20mm Ø 0.25" Pass
	Underfloor Heating	–	Suitable, max 27°C
	Static Electrical Propensity	EN 1815	2.0kV Classified as 'antistatic'
	Light Fastness	ISO 105-B02 (Method 3)	≥ 6
	VOC Emissions	Indoor Air Comfort GOLD AgBB/ABG FloorScore Finnish M1	Eurofins certified product Pass Certified Certified
	Responsible Sourcing	BES 6001	Excellent

Environmentally Preferable Flooring - Polyflor Forest fx PUR achieves a BRE Global A+ rating (ENP 415) in the Green Guide to Specification in use areas such as education and healthcare and is GreenTag LCA Rate certified with GreenRate level A - Gold Plus. Generic EN 15804 Environmental Product Declaration (EPD) available on request. Recyclable via the Recofloor scheme. Visit www.polyflor.com/sustainability.

PUR - Polyflor Forest fx PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low-cost, polish free maintenance regime for the lifetime of the flooring.

Hygiene - All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult **Polyflor Customer Technical Services** on +44 (0)161 767 1912, or email tech@polyflor.com.

*For safety flooring with sustainable wet slip resistance, refer to Polysafe ranges.

The data presented is correct at the time of printing. For latest information, please visit our website polyflor.com.

Decoration and shade may vary slightly from the samples shown.



BS EN 14041 EN 14041



UK Sales Direct: +44 (0)161 767 1122 | Export Sales Direct: +44 (0)161 767 1913
Sample Requests: +44 (0)161 767 2551 | email: info@polyflor.com | www.polyflor.com



January 2023 401/15