



TECHNICAL CHARACTERISTICS

DESCRIPTION				
Total thickness	EN ISO 24346 (EN 428)	mm	2.50	
Thickness of wearlayer	EN ISO 24340 (EN 429)	mm	0.30	
Weight: Mass per unit area	EN ISO 23997 (EN 430)	g/sqm	4660	
Size	EN ISO 24342 (EN 427)	cm	planks: 121.9 x 18.4	tiles: 61 x 61
Number of planks / tiles and sqm per box	EN ISO 24342 (EN 427)	planks / tiles	11 planks / 2.47 sqm	7 tiles / 2.60 sqm
CLASSIFICATION				
Norm / Product specification	-	-	EN ISO 10582	
European classification	EN ISO 10874 (EN 685)	class	23/31	
Fire rating - Classification	EN 13501-1	class	B _{fl} -s1	
Static electrical propensity	EN 1815	kV	< 2	
PERFORMANCE				
Wear Resistance	EN 660.2	mm ³	< 2.0	
Wear Group	EN 649	group	T	
Type binder content	ISO 10582	type	I	
Dimensional stability after exposure to heat	EN ISO 23999 (EN 434)	%	≤ 0.10	
Residual indentation	EN ISO 24343-1 (EN 433)	mm	≤ 0.10	
Sound insulation	EN ISO 717-2	dB	5	
Room impact noise	NF S 31074	dB	77	
Thermal conductivity	EN ISO 10456 (EN 12524)	W/(m.k)	0.25	
Colour fastness	EN 20 105 - B02	degree	≥ 6	
Surface treatment	-	-	PUR+	
Guarantee for residential use	-	year	12	
ENVIRONMENT / INDOOR AIR QUALITY				
TVOC after 28 days	ISO 16000-6	µg/m ³	< 100	
CE MARKING				
	EN 14041	   		

Areas of use: domestic use



PREMIUM