

Arquivinyl Disipativos

PRODUCT SPECIFICATION

Características

- > Láminas y losetas homogéneas en colores no direccionales
- > Propiedades de disipación estática [SD] para control estático
- > Excelente resistencia química y a la abrasión
- > Soldadura para crear un piso impermeable
- > Úselo con pulimentos conductores



Product Format	Standard	Result
Gauge	ISO 24346 (EN 428)	2.0mm
Total Weight	ISO 23997 (EN 430)	3030g/m ²

Sheet & Tile Sizes	Size	Shades	Quantity per Box	Coverage per Box/Roll
Sheet	2m x 20m	5	-	40m ²
Tile	608mm x 608mm	5	14	5.17m ²

Performance Requirements	Standard	Result
General Performance	ISO 10581 ASTM F1913 ASTM F1700	Conforms Conforms Conforms
Use Area	ISO 10874	34, 43
Slip Resistance	DIN 51130 / DIN EN 16165 Ann. B EN 13893	R9 Class DS
Binder Content	ISO 10581	Type I
Abrasion Resistance	EN 660-2	Group P
Reaction to Fire	EN 13501-1 ASTM E648 ASTM E662 CAN/ULC S102.2 AS ISO 9239-1	Class Bfl-S1 Class 1 <450 FSV < 300; SDV < 500 <8.0 kW/m ²
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Electrical Resistance	EN 1081 R ₁ /R ₂ ESD S 7.1 IEC 61340-4-1	1.0 x 10 ⁶ - 1.0 x 10 ⁹ ohms 1.0 x 10 ⁶ - 1.0 x 10 ⁹ ohms 1.0 x 10 ⁶ - 1.0 x 10 ⁹ ohms
All products require minimum 40% RH		

Sustainability	Standard	Result
BRE Green Guide		A+ Generic

Generic EN 15804 EPD	Available
Recyclable	100%
Recycled Content	25%
REACH	Compliant
Indoor Air Comfort Gold	Eurofins certified product
FloorScore	Certified
Finnish M1 Classification	Certified

Maintenance Performance

Standard

Result

Resistance to Chemicals	ISO 26987 (EN 423)	Good resistance
-------------------------	--------------------	-----------------

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

Hygiene

Standard

Result

Bacterial Resistance	ISO 846 Part C	Does not favour growth
----------------------	----------------	------------------------




BS EN 14041




EN 14041

Arquivinyl Disipativos


RANGE SHADES




Moonscape **5860** w/r 5260
NCS S 2005-Y40R LRV 55




Daybreak **5820** w/r 3130
NCS S 2500-N LRV 49



Lodestone **5830** w/r 3140
NCS S 4000-N LRV 33



Cascade **5800** w/r 5200
NCS S 3010-R80B LRV 38



Woodglade **5840** w/r 5240
NCS S 3005-G20Y LRV 41