

Arquivinyl Conductivos

PRODUCT SPECIFICATION

Características

- > Pisos laminados homogéneos en colores no direccionales
- > Conductivo electrostático [EC] para protección ESD
- > Excelente resistencia química y a la abrasión
- > Soldadura para crear un piso impermeable
- > Úselo con pulimentos conductores



Product Format	Standard	Result
Gauge	ISO 24346 (EN 428)	2.0mm
Total Weight	ISO 23997 (EN 430)	3060g/m ²

Sheet Size	Size	Shades	Quantity per Box	Coverage per Box/Roll
Sheet	2m x 20m	5	-	40m ²

Performance Requirements	Standard	Result
General Performance	ISO 10581 ASTM F1913	Conforms Conforms
Use Area	ISO 10874	34, 43
Slip Resistance	DIN 51130 / DIN EN 16165 Ann. B EN 13893	R9 Class DS
Binder Content	ISO 10581	Type I
Abrasion Resistance	EN 660-2	Group P
Reaction to Fire	EN 13501-1 ASTM E648	Class Bfl-S1 Class 1
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Electrical Resistance	EN 1081 R ₁ /R ₂ ESD S 7.1 IEC 61340-4-1 IEC 61340-4-5	1.0 x 10 ⁴ - 1.0 x 10 ⁶ ohms** ≤1.0 x 10 ⁹ ohms ≤1.0 x 10 ⁹ ohms <100v*

* Result when tested with conductive shoes, tested according to IEC 61340-4-3 and compliant to the requirements of IEC 61340-5-1

** Tested at 100V

Sustainability	Standard	Result
BRE Green Guide		A+ Generic
Generic EN 15804 EPD		Available
Recyclable		100%
Recycled Content		25%

REACH	Compliant
FloorScore	Certified
Finnish M1 Classification	Certified

Maintenance Performance	Standard	Result
Resistance to Chemicals	ISO 26987 (EN 423)	Good resistance

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

Hygiene	Standard	Result
Bacterial Resistance	ISO 846 Part C	Does not favour growth




BS EN 14041




EN 14041

Arquivinyl Conductivos


RANGE SHADES




Frosty Glen **6005** w/r 9834
NCS S1500-N LRV 65




Morning Dew **6006** w/r 6006
NCS S 2005-R70B LRV 53



Thunderstorm **6002** w/r 6002
NCS S 2500-N LRV 46



Tempest **6004** w/r 6004
NCS S 3020-R80B LRV 33



Warm Haze **6003** w/r 6003
NCS S1005-Y30R LRV 65