

Romeo y Julieta Lineal

TECHNICAL SPECIFICATION

Manufacturing method	:	Level loop
Pile type	:	Loop pile
Pile fibre	:	100% polypropylene solution-dyed
Gauge	:	1/10"
Pile weight	:	400 gr/m ²
Pile height	:	2.9 mm
Total weight	:	3700 gr/m ²
Total thickness	:	5.9 mm
Tuft density	:	193.550/m ²
Tile size	:	50 x 50 cm
Backing	:	Polyflex
Tiles per box	:	20

PERFORMANCE

Use classification	:	31
Caster chair test	EN 985	: B, occasional use
Abrasion	EN 1963	: Pass
Vettermann test	EN 1471	: Pass
Dimensional stability	EN 986	: Pass
Thermal isolation	ISO 8302	: 0.10 m ² K/W
Sound absorption	ISO 140-8	: 25 dB
Luxery class	:	LC1
DOP-nr	:	1016-3612
Prodis-nr	:	CDD4AC29

ELECTROSTATIC

Static loading	:	Anti-static
----------------	---	-------------

FLAMMABILITY

Reaction to fire	EN ISO 9239-1	: Cfl-s1
Reaction to fire	BS 4790	: Low radius of effect of ignition

COLOUR FASTNESS

Light	ISO 105 B02	: 7.0 - 8.0
Rubbing	ISO 105 x12	: 5.0

MAINTENANCE

Regular vacuum cleaning is essential. Spills and surface stains can be removed by sponging with a damp cloth, or for more resistant stains, with a mild detergent solution.

