

Conceptline PUR

PRODUCT SPECIFICATION

Key Features

- > Parquet & wood designs
- > Co-ordinating inlay accessories available
- > Low VOC emissions
- > Designed for light commercial & residential interiors



Product Format	Standard	Result
Gauge	ISO 24346 (EN 428)	2.0mm
Wear Layer	ISO 24340 (EN 429)	0.3mm
Total Weight	ISO 23997 (EN 430)	3600g/m ²
Finish		PUR

Plank & Tile Sizes	Size	Shades	Quantity per Box	Coverage per Box/Roll
Plank	76.2mm x 228.6mm	2	192	3.34m ²
	184.2mm x 1219.2mm	8	15	3.37m ²

Performance Requirements	Standard	Result
General Performance	ISO 10582 (EN 649)	Conforms
Use Area	ISO 10874 (EN 685)	23, 31
Slip Resistance	EN 13893 DIN 51130 / DIN EN 16165 Ann. B	Class DS R10
Binder Content	ISO 10582	Type I
Abrasion Resistance	EN 649	Group T
Reaction to Fire	EN 13501-1	Class Bfl-S1
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Residual Indentation	ISO 24343-1 (EN 433)	<0.05mm*
Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
Dimensional Stability	ISO 23999 (EN 434)	≤0.10%*
Underfloor Heating		Suitable, max 27°C
Light Fastness	ISO 105-B02 (Method 3)	≥6

*Average test value from current production.

Sustainability	Standard	Result
Product Specific EPD	EN 15804+A2	Available
Recyclable		100%

Recycled Content		Up to 40%
Indoor Air Comfort Gold		Eurofins certified product
FloorScore		Certified
Responsible Sourcing	SA 8000	Approved Factory

Maintenance Performance	Standard	Result
Resistance to Chemicals	ISO 26987 (EN 423)	Good resistance

Regular light maintenance is more cost-effective than periodic heavy maintenance and more beneficial to the floor covering.



Polyflor Ltd. Head Office

PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: info@polyflor.com • www.polyflor.com

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

Conceptline PUR



RANGE SHADES

76.2mm x 228.6mm
3" x 9"



Traditioxnal Grey Oak Parquet **3801**
LRV 32



Christchurch Oak Parquet **3802**
LRV 27

184.2mm x 1219.2mm
7.25" x 48"



Traditional Grey Oak **3037**  LRV 32



Christchurch Oak **3481**  LRV 27



Snowhill Oak **3181**  LRV 51



Bridstow Oak **3183**  LRV 37



Bay Oak **3182**  LRV 38



Maldon Oak **3185**  LRV 22



Monarch Oak **3184**  LRV 51



Parkland Oak **3804**  LRV 29

LRV - Light Reflectance Value

 Micro Bevelled Edges

 Colour/Pattern Variation

Polyflor Ltd. Head Office

PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: info@polyflor.com • www.polyflor.com

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.