

Ultima Cook 55

PRODUCT SPECIFICATION

Características

- > Suelo de seguridad vinílico de 3 mm extremadamente duradero
- > Prueba de péndulo: 55+ (deslizante: 96)
- > Mayor resistencia al deslizamiento para soportar contaminantes de alta viscosidad
- > Uniones soldadas para un acabado impermeable
- > Suelo de seguridad especializado, diseñado para cocinas comerciales y áreas de producción de alimentos



Product Format	Standard	Result
Gauge	ISO 24346 (EN 428)	3.0mm
Total Weight	ISO 23997 (EN 430)	3600g/m ²

Sheet Size	Size	Shades	Quantity per Box	Coverage per Box/Roll
Sheet	2m x 15m	8	-	30m ²

Performance Requirements	Standard	Result
General Performance	EN 13845 ASTM F1303	Conforms Type II, Grade I, Class B Backing
Use Area	ISO 10874 (EN 685)	23, 34, 43
Enhanced Slip Resistance	EN 13845 AS 4586 RRL Pendulum Test DIN 51130 / DIN EN 16165 Ann. B ASTM D2047	ESf R12 ≥55 (wet test - 4S Rubber / Slider 96) R12 SCOF >0.8
Abrasion Resistance	EN 13845	50,000 cycles
Reaction to Fire	EN 13501-1 ASTM E648 CAN/ULC S102.2 AS ISO 9239-1	Class Bfl-S1 Class 1 FSV < 300; SDV < 500 >8.0kW/m ²
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Residual Indentation	ASTM F970 (Modified)	≤0.005" (750psi)
Resistance to Light	ASTM F1515	ΔE ≤ 8.0 - Meets
Resistance to Heat	ASTMF1514	ΔE ≤ 8.0 - Meets

Sustainability	Standard	Result
BRE Green Guide		A+ Generic
Generic EN 15804 EPD		Available
Recyclable		100%
Recycled Content		Contains recycled material

REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product
FloorScore		Certified
Finnish M1 Classification		Certified
AgBB/ABG		Pass
Responsible Sourcing	BES 6001	Excellent

Maintenance Performance	Standard	Result
Resistance to Chemicals	ISO 26987 (EN 423) ASTM F925	Good resistance Good resistance
Alco Hand Gels	Compatible for use with most commonly used alco-based hand gels	
Steam Cleaning	Suitable for steam cleaning on a periodic basis	

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

Hygiene	Standard	Result
Bacterial Resistance	ISO 846 Part C	Does not favour growth



BS EN 14041



EN 14041