

# AUTOADHESIVAS

## CARACTERÍSTICAS TÉCNICAS

|                                              |                         |                   | Planks                                   | Tiles       |
|----------------------------------------------|-------------------------|-------------------|------------------------------------------|-------------|
| <b>DESCRIPTION</b>                           |                         |                   |                                          |             |
| Total thickness                              | EN ISO 24346 (EN 428)   | mm                | 2.00                                     | 2.00        |
| Thickness of the wear layer                  | EN ISO 24340 (EN 429)   | mm                | 0.20                                     | 0.20        |
| Weight / Mass per unit area                  | EN ISO 23997 (EN 430)   | g/sqm             | 3920                                     | 3425        |
| Size                                         | EN ISO 24342 (EN 427)   | cm                | 91.4 x 15.2<br>91.4 x 18.4               | 30.5 x 60.9 |
| Plank or tiles per box                       | -                       | planks / tiles    | 16                                       | 12          |
| Area per box                                 | -                       | sqm               | 2.20 (91.4 x 15.2)<br>2.69 (91.4 x 18.4) | 2.22        |
| <b>CLASSIFICATION</b>                        |                         |                   |                                          |             |
| Norm / Product specification                 | -                       | EN 649            | EN 649                                   | EN 649      |
| European classification                      | EN ISO 10874 (EN 685)   | class             | 22                                       | 22          |
| Fire rating - Classification                 | EN 13501-1              | class             | Bfl S1                                   | Bfl S1      |
| Static electrical propriety                  | EN 1815                 | -                 | < 2 kV                                   | < 2 kV      |
| Slip resistance wet: ramp test with oil      | DIN 51130               | class             | R9                                       | R9          |
| <b>PERFORMANCE</b>                           |                         |                   |                                          |             |
| Wear Group                                   | EN 649                  | group             | T                                        | T           |
| Dimensional stability after exposure to heat | EN ISO 23999 (EN 434)   | %                 | ≤ 0.25                                   | ≤ 0.25      |
| Residual Indentation                         | EN ISO 24343-1 (EN 433) | mm                | 0.05                                     | 0.05        |
| Impact sound insulation                      | EN ISO 717-2            | dB                | 3                                        | 3           |
| Room impact noise                            | NF S 31074              | class             | C                                        | C           |
| Thermal conductivity                         | EN ISO 10456 (EN 12524) | W(m.k)            | 0.25                                     | 0.25        |
| Colour fastness                              | EN 20 105 - B02         | degree            | ≥ 6                                      | ≥ 6         |
| Surface treatment                            | -                       | -                 | PUR                                      | PUR         |
| Garantee for residential use                 | -                       | year              | 10                                       | 10          |
| <b>ENVIRONMENT / INDOOR AIR QUALITY</b>      |                         |                   |                                          |             |
| TVOC after 28 days                           | ISO 16000-6             | µg/m <sup>3</sup> | < 100                                    | < 250       |
| VOC rating (French norm)                     | -                       | -                 | A+                                       | A+          |

### CE MARKING



EN 14041



**Areas of use:** domestic use



#### HEALTH

- Formaldehyde-free
- Lead-free, no heavy metals
- Solvent-free
- No harmful plasticizer
- Low VOC emission

#### ENVIRONMENT

- ISO 14001
- Soapy water cleaning