


Ficha Tecnica

	Gauge	EN 428/ISO 24346	1.5mm, 2.0mm, 2.5mm 3.0mm
	Roll Size	EN 426/ISO 24341	1.5mm: 2m x 27.5m = 55m ² 2.0mm: 2m x 20m = 40m ² 2.5mm: 2m x 15m = 30m ² 3.0mm: 2m x 13m = 26m ²
	Tile Size	EN 427/ISO 24342	2.0mm: 300mm x 300mm = 4.5m ² 2.5mm: 300mm x 300mm = 3.6m ² 3.0mm: 300mm x 300mm = 2.97m ² 2.0mm: 608mm x 608mm = 5.17m ²
	Total Weight	EN 430/ISO 23997	1.5mm: 2360g/m ² 2.0mm: 3200g/m ² 2.5mm: 4200g/m ² 3.0mm: 5010g/m ²
	General Performance	EN 649/EN ISO 10581 ASTM F1913 ASTM F1700	Conforms Conforms Conforms
	Use Area	EN 685/ISO 10874	
	Reaction to Fire	EN 13501-1 ASTM E662* ASTM E648*	Class Bfl-S1 <450 Class 1 *1.5mm, 2.0mm
	Abrasion Resistance	EN 660-2 EN ISO 10581	Group M Type II
	Slip Resistance	EN 13893 AS 4586	Class DS R9
	Residual Indentation	ASTM F970 (Modified)	Static load 750psi
	Electrical behaviour (body voltage)	EN 1815	≤2kV Classified as 'antistatic'
	Castor Chair (continuous use)	EN 425/ISO 4918	Suitable
	Maritime Usage	Marine Equipment Directive 2014/90/EU* SOLAS 74*	Conforms Conforms *2.0mm
	VOC Emissions	Indoor Air Comfort GOLD AgBB VOC test Floorscore* Finnish M1 Classification* Swedish B.P.D (FLEC test) GBCA/NZGBC Green Star IEQ-VOC	Eurofins certified product Pass Certified Pass Best Class Compliant *1.5mm, 2.0mm 2.0mm

Responsible Sourcing

BES 6001

Very Good

Environmentally Preferable Flooring - Polyflor Standard XL achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 472) in major use areas such as education and healthcare and is GreenTag LCA Rate certified with GreenRate level A - Gold Plus. Generic EN 15804 Environmental Product Declaration (EPD) available on request. Standard XL is 100% recyclable and contains 25% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/sustainability.

Hygiene - All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

Polyflor homogeneous PUR, heterogeneous PUR and Polysafe safety flooring ranges are compatible for use with the most commonly used alco-based hand gels. Some alco-based hand gels contain a high concentration of ethanol and to discuss their compatibility with Standard XL, contact Polyflor Customer Technical Services. For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

The data presented is correct at the time of printing. For latest information, please visit our website polyflor.com.

Decoration and shade may vary slightly from the samples shown.

