

PEARLAZZO PUR

- BRE Global Environmental Generic A+ Rating for contract applications
- Attractive, high-performance, heavy duty floorcovering
- Polyurethane reinforcement for a low cost, lifetime polish-free maintenance regime

SPECIFICATION



2.0mm



2m x 20m = 40m²



2950g/m²



GENERAL PERFORMANCE

EN 649
ASTM F1913

Agrément – under application



REACTION TO FIRE

EN 13501-1 Class Bfl-S1 { EN ISO 9239-1 ≥8kw/m²
EN ISO 11925-2 Pass

ASTM E662 <450

ASTM E648 Class 1



SLIP RESISTANCE

EN 13893 Class DS
AS/NZS 4586 R9



ABRASION RESISTANCE

EN 660 Part 2 Group T



ELECTRICAL BEHAVIOUR (body voltage)

EN 1815 This product does not accumulate static charges above 2kV and is classified as 'antistatic'. For specialist applications where there is a requirement to dissipate the electrostatic charge, see the Polyflor ESD product ranges.



VOC EMISSIONS

AgBB VOC test: Pass
Floorscore certified (SCS Certificate Reg No: SCS-FS-02034)
Finnish M1 Classification: Pass



CASTOR CHAIR

(continuous use)
Suitable



INDENTATION RESIDUAL

ASTM F970 (Modified)
Static load 750psi



ENVIRONMENTALLY PREFERABLE FLOORING

Vinyl flooring has a generic BRE A+/A Rating in the Green Guide to Specifications for contract applications. Polyflor Pearlazzo PUR is 100% recyclable and contains 25% recycled material. A full Environmental Report detailing Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance can be found at www.polyflor.com/environment



HYGIENE

This product has been independently tested and results demonstrate that it inhibits the growth of MRSA on the flooring. An effective cleaning regime is however, the most important defence against infection.



Pearlazzo PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low cost, polish-free maintenance regime for the lifetime of the flooring.



APPLICATIONS

Polyflor Pearlazzo PUR is recommended for heavy traffic areas that require a hardwearing floorcovering which is attractive, modern and easy to maintain. Such areas include banking halls, retail showrooms, department stores, hotels, restaurants, leisure centres, universities, hospitals, health clinics, libraries, commercial offices and public reception areas.



Polyflor homogeneous PUR ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For clarification and for information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.



POLYFLOR
PEARLAZZO PUR
HOMOGENEOUS



PERFORMANCE AND
PROPERTIES



† Refer to BRE Global ratings on www.thegreenguide.org.uk



POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM
UK SAMPLE REQUESTS: +44 (0)161 767 2551

James Hulstead
FLOORING

