
Polysafe Quattro PUR

Polysafe Quattro PUR is a heavy-duty, carborundum-free safety flooring with a flat emboss, designed to provide underfoot traction in continually wet areas. Available in either a solid colour or tonal chipped decoration, Quattro is ideally suited to both barefoot and shod traffic. Incorporating particles in the vinyl for sustainable wet slip resistance. Quattro offers enhanced protection in areas such as walk-in showers, wet rooms, disabled adaptations, hydrotherapy areas, spas, changing rooms and indoor swimming pool surrounds.









EN 685/ISO 10874









Resistance to Chemicals

Enhanced Slip Resistance

Water Tightness	EN 13553	Annex A
Reaction to Fire	EN 13501-1 ASTM F648	Class Bfl-S1



Australian BCA Spec C1.10-3 Complies EN 13845 50,000 cycles Abrasion Resistance EN 649 Group T



EN 13845 ESb & ESf AS 4586 Appendix A AS 4586 Appendix C AS 4586 Appendix D Class B R11 DIN 51097 Class B

EN 423



DIN 51130 R11 RRL Pendulum Test >50 (wet test - 4S Rubber/Slider 96) Surface Roughness Rz ≥20µm





SSSS



Environmentally Preferable Flooring - Polysafe Quattro PUR achieves BRE Global Environmental Generic A+ rating in major use areas such as education and healthcare and is GreenTag LCA Rate certified with GreenRate level A - Gold Plus. Generic EN 15804 Environmental Product Declaration (EPD) available on request. It is 100% recyclable and contains recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/sustainability.

Polysafe PUR - Polysafe Quattro PUR features a high quality, cross-linked polyurethane reinforcement. UV cured to provide superior cleaning benefits, life cycle maintenance savings and optimum appearance retention. As with all Polysafe products, Polysafe Quattro PUR should not have a polish applied.



Hygiene - All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.



Polysafe safety flooring ranges have good resistance to dilute acids and alkalis, are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. Chemical resistance charts available on request. For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or

The data presented is correct at the time of printing. For latest information, please visit our website polyflor.com. This product contains a blend of quartz particles in various colours within the vinyl to impart the required sustainable slip resistance. Decoration and shade may vary slightly from the samples shown.



























