

The Secura luxury vinyl sheet collection features a selection of 22 wood, stone and abstract designs, to complement a variety of interiors. Attractive yet practical, Secura offers 19dB impact sound reduction and is durable and easy to maintain. Available in 2,3 and 4 metre roll widths, Secura is also looselay meaning no adhesive is required.

Ideally suited for use in residential and light commercial applications.



	Gauge	EN 428/ISO 24346	3.0mm
	Wear Layer	EN 429/ISO 24340	0.35mm
	Roll Size	EN 426/ISO 24341	4m x 25m = 100m ² 3m x 25m = 75m ² 2m x 25m = 50m ²
	Total Weight	EN 430/ISO 23997	1780g/m ²
	General Performance	EN 653 EN ISO 26986	Conforms Conforms
	Use Area	EN 685/ISO 10874	
	Acoustic Impact Sound Reduction	EN ISO 140-8 EN ISO 10140-3	≥19dB ≥19dB
	Resistance to Chemicals	EN 423 ISO 26987	Excellent chemical resistance
	Reaction to Fire	EN 13501-1	Class Bfl-S1
	Abrasion Resistance	EN 653	Group T
	Slip Resistance*	EN 13893 AS 4586 DIN 51130	Class DS (dry condition) R10 R10
	Indentation Residual	EN 433/ISO 24343-1	<0.2mm
	Dimensional Stability	EN 434/EN ISO 23999	<0.40%
	Flexibility	EN 435/EN ISO 24344	(Method A) / Pass 20mm Ø
	Thermal Resistance	ISO 8302	Suitable for underfloor heating 0.0525m ² K/W 0.525 Tog
	Electrical behaviour (body voltage)	EN 1815	≤2kV Classified as 'antistatic'
	Light Fastness	ISO 105-B02	(Method 3) ≥6
	Castor Chair (continuous use)	ISO 4918	Pass. Suitable for castor chairs.
	Furniture Leg	EN 424	Pass. Type 2 foot
	VOC Emissions	Indoor Air Comfort GOLD Floorscore	Eurofins certified product Certified Product
	Responsible Sourcing	BES 6001	Very Good

Environmentally Preferable Flooring - Polyflor Secura achieves BRE Global A rating (Generic) in the Green Guide to Specification in uses areas such as education and healthcare. It is 100% recyclable. Visit www.polyflor.com/sustainability.

PUR - Polyflor Secura features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low-cost, polish free maintenance regime for the lifetime of the flooring.



Hygiene - All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.



For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

*For safety flooring with sustainable wet slip resistance, refer to Polysafe ranges.

The data presented is correct at the time of printing. For latest information, please visit our website polyflor.com.

Decoration and shade may vary slightly from the samples shown.

