

Arquisafe Madera PUR



| | | | |
|--|--|--|---|
| | Gauge | EN 428/ISO 24346 | 2.0mm |
| | Wear Layer | EN 429/ISO 24340 | 0.70mm |
| | Roll Size | EN 426/ISO 24341 | 2m x 20m = 40m ² |
| | Total Weight | EN 430/ISO 23997 | 2780g/m ² |
| | General Performance | EN 13845 ASTM F1303 | Conforms Conforms |
| | Use Area | EN 685/ISO 10874 | |
| | Resistance to Chemicals | EN 423 | Good chemical resistance |
| | Reaction to Fire | EN 13501-1 ASTM E648 | Class Bfl-S1 Class 1 |
| | Abrasion Resistance | EN 13845 EN 649 | 50,000 cycles Group T |
| | Enhanced Slip Resistance | EN 13845 AS 4586 DIN 51130 RRL Pendulum Test Surface Roughness | ES1 R10 R10 ≥36 (wet test - 4S Rubber/Slider 96) Rz ≥20µm |
| The wet slip resistance across all Polysafe products is sustainable throughout the guaranteed life of the product, with strict adherence to HSE Guidelines. For further clarification regarding slip resistance, consult Polyflor. | | | |
| | Electrical behaviour (body voltage) | EN 1815 | ≤2kV Classified as 'antistatic' |
| | VOC Emissions | Indoor Air Comfort GOLD AgBB VOC test Floorscore | Eurofins certified product Very low emissions Certified |
| | Responsible Sourcing | BES 6001 | Very Good |
| | Agrément Assurance - has been independently assessed by the British Board of Agrément and product performance is assured for at least 10 years in recommended use areas. With proper maintenance, the appearance, colour and slip resistance will be retained during this period. | | |
| | Environmentally Preferable Flooring - achieves BRE Global A+ rating (ENP 472) in the Green Guide to Specification in use areas such as education and healthcare and is GreenTag LCA Rate certified with GreenRate level A - Gold Plus. Generic EN 15804 Environmental Product Declaration (EPD) available on request. It is 100% recyclable and contains recycled material. Recyclable via the Recofloor scheme. | | |
| | features a high quality, cross-linked polyurethane reinforcement, UV cured to provide superior cleaning benefits, life cycle maintenance savings and optimum appearance retention. As with all products, should not have a polish applied. | | |
| | Hygiene - All commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection. | | |
| | flooring ranges have good resistance to dilute acids and alkalis, are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. Chemical resistance charts available on request. For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult | | |
| | As with all products, should not have a polish applied. | | |
| | The data presented is correct at the time of printing. For latest information, please visit our website | | |
| | Decoration and shade may vary slightly from the samples shown. | | |

