

PERLADO 2mm



PAVIMENTOS
ARQUISERVI

FICHA TECNICA

Gauge		2.00mm	
Roll Size		2m x 20m = 40m ²	
Product Weight		2950g/m ²	
General Performance		EN 649 ASTM F1913 Agrément – under application	 10 EN 14041:2004 EN 649
Use Area Classification		23, 34, 43	
Reaction to Fire		EN 13501-1 Class Bfl-S1 EN ISO 9239-1 ≥8kw/m ² EN ISO 11925-2 Pass ASTM E662 <450 ASTM E648 Class 1	
Slip Resistance		EN 13893 Class DS AS/NZS 4586 R9	
Abrasion Resistance		EN 660 Part 2 Group T	
Electrical Behaviour (body voltage)		EN 1815 This product does not accumulate static charges above 2kV and is classified as 'antistatic'. For specialist applications where there is a requirement to dissipate the electrostatic charge, see the ESD product ranges.	
VOC Emissions		AgBB VOC test: Pass Florescore certified (SCS Certificate Reg No: SCS-FS-02034)	
Environmentally Preferable Flooring		Vinyl flooring has a generic BRE A+/A Rating in the Green Guide to Specifications for contract applications. is 100% recyclable and contains 25% recycled material. A full Environmental Report detailing achievements in areas such as recycling, energy reduction and waste avoidance can be found at:	
Hygiene		This product has been independently tested and results demonstrate that it inhibits the growth of MRSA on the flooring. An effective cleaning regime is however, the most important defence against infection.	
Maintenance		features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low cost, polish-free maintenance regime for the lifetime of the flooring.	
Applications		is recommended for heavy traffic areas that require a hardwearing floorcovering which is attractive, modern and easy to maintain. Such areas include banking halls, retail showrooms, department stores, hotels, restaurants, leisure centres, universities, hospitals, health clinics, libraries, commercial offices and public reception areas.	
Notes		Polyflor homogeneous PUR ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For clarification and for information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, .	