

DESCRIPTION	STANDARDS	PVC CONTINUO MOTEADO
Construction	Non-directional homogeneous flooring	
Product specification (Binder content)	EN ISO 10581	Type I.
Total thickness	EN ISO 24346	2.0 mm
Width of roll	EN ISO 24341	2 m
Length of roll	EN ISO 24341	20 lm
Total weight	EN ISO 23997	2.8 kg/m ²

CLASSIFICATION

European classification	EN ISO 10874	class: 34/43
Residual indentation	EN ISO 24343	max 0.1 mm
Dimensional stability	EN ISO 23999	max 0.2 %
	EN ISO 23999	average 0.1 %
Curling	EN ISO 23999	max. 8 mm

PERFORMANCE

Fire resistance	EN 13501-1	Class: Bfl-s1
Slip resistance	DIN 51130	R9
	EN 13893	Class: DS
Castor chair resistance	EN ISO 4918	✓
Light fastness	EN 20105 B02	grade 6
Thermal resistance	EN 12524	0.012 m ² K/W
Chemical resistance	EN ISO 26987	✓
Bacteriostatic activity	ISO 22196	>99%
Surface treatment	Silver Knight iGUARD	
Environmental attributes	Phthalate-, solvent and heavy metal free	
Seaming method	heat or cold weld	
VOC emission	ISO 16000-6	<10 µg/m ³ (after 28 days)
Formaldehyde emission	ENV 717-1	E1 (no emission)